

BIOMICROGEL® REAGENTS FOR PALM OIL EXTRACTION: PROBLEMS TO BE SOLVED

The process of producing palm oil has not changed for the last 50 years. We have just improved it so you can earn more and:

- Increase OER (CPO extraction)
- Reduce oil losses
- Make oil processing faster and easier

- Save money on expensive equipment
- Reduce water consumption
- Not affect the quality of the oil or its characteristics



BIOMICROGEL® FOR PALM OIL EXTRACTION: HOW IT WORKS

Biomicrogel® is a new technology for production of biopolymers from agricultural waste

These biopolymers substitute standard synthetic polymers, making oil extraction more efficient, cost-effective and sustainable

Watch Biomicrogel® effect in our YouTube video










BIOMICROGEL® FOR PALM OIL EXTRACTION: HOW IT WORKS

Biomicrogel® helps to release oil trapped between fruits residue, boosting oil extraction



- Biomicrogel® added to DCO forms a biopolymer nanolayer on the surface of suspended solids in the sludge, speeds up oil extraction in the clarifier
- Negatively charged biopolymer molecules are attached to positively charged solid particles' surface and repel droplets of oil



BIOMICROGEL® FOR PALM OIL EXTRACTION: ADVANTAGES

Biomicrogel® presents significant advantages for factories to increase productivity without CAPEX investments and translates in attractive Economic Value Added effect

Increases OER extraction by 0.5-1.3 p.p. for CPO, and 15 p.p. for SPO

Works with temperatures up to 100°C and does not affect the quality of the oil

Reduces extraction time and water consumption up to 50%

No changes needed in Mills operating procedures, low implementation and running costs

Reduces oil losses in Underflow, Heavy Phase, Cake and Mill effluent (POME) BMG can be dissolved in hot or cold water

Reduces moisture content in SPO (from 17% to 0.9%)

Works with Empty Bunch Liquor and Palm Kernel Oil



BIOMICROGEL® FOR PALM OIL EXTRACTION: PRODUCTS

Biomicrogels Group offers several solutions in Upstream and Downstream of palm oil extraction process



BMG-C4

Increases vegetable oil extraction and reduces oil losses



BMG-SPO

Extracts 25% more quality SPO twice as fast without additional equipment



BMG Dosing Station

Easy to integrate and operate with low running costs




BMG HERO

Recovers 80% of oil in POME



BIOMICROGEL® FOR PALM OIL EXTRACTION: INTEGRATION IN PALM OIL MILL PROCESS




Mills operating procedures remain the same.

BMG solution integrates without major costs and changes to the extraction process



BIOMICROGEL® FOR PALM OIL EXTRACTION: LAB TESTS RESULTS



Oil level vs time curve, 3% BMG solution, Dosing 1 g/l

We carried out multiple tests at Indonesian and Malaysian factories and each of them showed increase in oil extraction by up to 10-80% after one hour





BIOMICROGEL® FOR PALM OIL EXTRACTION: LAB TESTS RESULTS – SLUDGE PALM OIL

Task


Demonstrate BMG effect in lab tests

Lab test method

• COT and Underflow samples taken Biomicrogel® BMG-C4 used in BMG tube Control tube and BMG tube placed in the water bath, heated to 90°C

Results

- Increased oil layer in COT sample by 100% after 75 minutes of settling
- 10 mm of oil in Underflow sample vs 5 mm in Control sample after 60 minutes of settling



COT sample Underflow sample



BIOMICROGEL® FOR PALM OIL EXTRACTION: LAB TESTS RESULTS – SLUDGE PALM OIL

Task


Demonstrate BMG application for Sludge Palm Oil

Lab test method

- Sludge palm oil samples taken
- Biomicrogel® BMG-C4 used in BMG tube
- Control tube and BMG tube placed in the water bath, heated to 90°C

Results

After one hour BMG extracts 28-40% more oil, and oil in sludge looks better separated from solid



Visible oil separation after 1 hour



BIOMICROGEL® FOR PALM OIL EXTRACTION: HERO EQUIPMENT RESULTS

- HERO High Efficiency Recovery Oil equipment for extracting oil from POME
- 6 contracts signed including Felda and Felkra Groups
- ✓ HERO can recover 80% of oil in POME after 1 hour retention time.
- Recovered oil in the latest case in Malaysia had FFA 10.09% and moisture 0.44%







BIOMICROGEL® FOR PALM OIL EXTRACTION: PRODUCT EXAMPLE



Physical properties of BMG-C4

Aggregate state	Powder
Color	Varies from beige to yellow-brown
Bulk density	0.55 - 0.60 g/m ³
pH value*	1.4 - 6.5

^{*}The concentration of the aqueous solution should not exceed 3%

Package

BMG-C4 is supplied in 25 kg sealed bag



BIOMICROGEL® BMG-C4 TECHNICAL INFORMATION

Application

BMG-C4 is designed to increase the extraction of various vegetable oils during their production at the stages of settling and centrifugation. A water solution of BMG-C4 has the property to separate oil from solid particles.

BMG-C4 is used as a 3% working solution

Recommended dosage

The optimal dosage of the BMG-C4 is from 0.7 to 1.0 g of BMG-C4 dry powder per 1 litre of non-oil sludge in DCO flow. BMG-C4 dosage is calculated based on the combined volume of water, non-oil-solid and emulsion, or volume of sludge minus oil volume

It is recommended to add in the form of a 3% water working solution. The volume of working solution BMG-C4 is from 10 to 33 ml per 1 litre of non-oil sludge in DCO flow

Preparation of the working solution

The working solution of BMG-C4 is prepared in a tank equipped with an overhead stirrer at a stirring speed of 100 rpm by dissolving an appropriate amount of dry BMG-C4 powder in tap or hot water that. The dissolution time varies from 10 to 30 minutes

To prepare a working solution with 3% concentration – take 30 kg of BMG-C4 dry powder, pour it into a mixing tank and add 970 litre of tap water. The recommended stirring time is 20-30 minutes, or until BMG-C4 is completely dissolved

Safety data

Sodium carboxymethyl cellulose, (CAS-No.) 9004-32-4, (EC-No.) 618-378-6 BMG safety confiirmed by independent expertise in test centers in Malaysia and Indonesia













BIOMICROGELS GROUP: ABOUT THE COMPANY

We have been producing industrial reagents for more than 12 years Registered more than 100 patents globally

Our products are applied for:


- Home care and cosmetics products
- Mineral processing


Industrial wastewater treatment

Vegetable oils extraction

Recognized as a game changer by the Palm Oil leading experts:
















BIOMICROGELS GROUP: ABOUT THE COMPANY

Product development for customer needs

- Own research and development center
- 4 modern laboratories
- Doctor and candidates of chemical sciences on staff

Modern manufacturing

- 3000 m² production area
- 10 tons of finished products per shift








BIOMICROGELS GROUP: BMG IMPLEMENTATION FLOW-CHART

We collect samples, conduct laboratory and industrial tests, and accompany you at all stages Before delivery, we will prove that Biomicrogel® products are guaranteed to solve your tasks



BIOMICROGELS GROUP: AWARDS



Winner in the «Green Development» category in the BRICS Innovation competition 2023



The Best Tech Company at G20, Italy 2021



«Seal of quality» of the European program on implementation of innovations Horizon 2020



Included in the ranking of the 100 most promising companies in the world



Winner of the international innovation development program Poland Prize



«Best Technology» at the international environmental award EWA AWARDS 2020



BIOMICROGELS GROUP: CONTACTS

Contact us:



info@biomicrogel.com



+7 (343) 363-38-01



www.biomicrogel.com/my/

